

FIAT GRANDE PANDA		RED (ELECTRIC)	LA PRIMA (ELECTRIC)	POP (HYBRID)	ICON (HYBRID)	LA PRIMA (HYBRID)
DIMENSIONS	Length [mm]	3,999	3,999	3,999	3,999	3,999
	Height [mm]	1,570	1,573	1,586	1,586	1,585
	Height (w/ Antenna) [mm]	1,581 on antenna fixed base	1,615 on roof rails	antenna not present	1,598 on antenna fixed base	1,629 on roof rails
		(1,801 on antenna removable part)	(1,803 on antenna removable part)		(1,818 on antenna removable part)	(1,818 on antenna removable part)
	Width [mm]	1,763	1,763	1,763	1,763	1,763
	Width (w/ Mirrors) [mm]	2,017	2,017	2,017	2,017	2,017
	Wheelbase [mm]	2,540	2,540	2,540	2,540	2,540
	Wheelsize	TOD 632	TOD 638	TOD 652	TOD 652	TOD 658
	Front Overhang [mm]	788	788	788	788	788
	Rear Overhang [mm]	671	671	671	671	671
	Ground Clearance [mm, standard A]	137	137	137	137	137
		361 l	361 l	412 l	412 l	412 l
	Boot volume [L]	(350 liquid above carpet + 11 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 11 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)
		1,315 l	1,315 l	1,366 l	1,366 l	1,366 l
	Boot volume w/ folded seats [L]	(1,304 liquid + 11 bricks below trunk carpet without tyre kit cargo box)	(1,304 liquid + 11 bricks below trunk carpet without tyre kit cargo box)	(1,304 liquid + 62 bricks below carpet without tyre kit cargo box)	(1,304 liquid + 62 bricks below carpet without tyre kit cargo box)	(1,304 liquid + 62 bricks below carpet without tyre kit cargo box)
Tire Information	205/55R16	205/50R17	205/60R16	205/60R16	205/55R17	
Number of Seats	5	5	5	5	5	
BRAKES	Front	Disc	Disc	Disc	Disc	Disc
	Rear	Disc	Disc	Disc	Disc	Disc
SUSPENSIONS	Front	Mac Pherson	Mac Pherson	Mac Pherson	Mac Pherson	Mac Pherson
	Rear	Twist Beam	Twist Beam	Twist Beam	Twist Beam	Twist Beam
STEERING	Power (torque max / Absorption)	75Nm (100A max)	75 Nm (100A max)	75Nm (100A max)	75Nm (100A max)	75 Nm (100A max)
	Ratio	51,5 mm/rev	51,5 mm/rev	51,5 mm/rev	51,5 mm/rev	51,5 mm/rev
	Turn lock to lock (revs / deg)	3,1 / 1118	3,1 / 1118	3,1 / 1118	3,1 / 1118	3,1 / 1118
WEIGHTS	Kerb to kerb turning cycle [m]	10,9	10,9	10,9	10,9	10,9
	Kerb Weight [kg]	1,532	1,554	1,315	1,327	1,347
	Weight Standard A [kg]	1,457	1,479	1,240	1,252	1,272
	Max Payload (including driver) [kg]	453	431	460	448	428
	Battery [kg]	350	350	12	12	12
Towing [kg]	550	550	600	600	600	
PERFORMANCES * provisional data under homologation	Max Power [kW]	83	83	74	74	74
	Max Power [CV]	113	113	100	100	100
	Max Torque [Nm]	122	122	205	205	205
	Traction	FWD	FWD	FWD	FWD	FWD
	WLTP Consumption - Combined [kWh/100km]	16,8	16,8	-	-	-
	WLTP Range - Combined [km]	320	320	-	-	-
	CO2 Emissions - Combined [g/km]	-	-	123*	123*	123*
	Consumption - Combined [l/100 km]	-	-	5,4*	5,4*	5,4*
	Top Speed [km/h]	132	132	160*	160*	160*
	Acceleration 0-100 km/h [s]	11	11,5	10*	10*	10*
	Acceleration 0-50 km/h [s]	4,2	4,2	-	-	-
	Technology	LFP	LFP	NMC	NMC	NMC
BATTERY AND CHARGING	Total Voltage (Volts)	400V	400V	48V	48V	48V
	Battery Capacity [kWh]	44kWh	44kWh	0,876kWh	0,876kWh	0,876kWh
	Battery Capacity (Net) [kWh]	43,8	43,8	-	-	-
	Charge Port	CCS Type2	CCS Type2	-	-	-
		+ spiral cable	+ spiral cable	-	-	-
	AC On-Board-Charger [kW]	7kW (11kW + NO spiral cable OPT)	7kW (11kW + NO spiral cable OPT)	-	-	-
	DC Fast Charger [kW]	100kW	100kW	-	-	-
	Charging Time [h:min] (AC 7kW - 20-80%)	04:20	04:20	-	-	-
	Charging Time [h:min] (AC 11kW - 20-80%)	02:50	02:50	-	-	-
Charging Time (DC 100kW - 20-80%)	00:27	00:27	-	-	-	
ENGINE	Type	M2 EDM	M2 EDM	EB2LTEDH2 3 CYL TURBO	EB2LTEDH2 3 CYL TURBO	EB2LTEDH2 3 CYL TURBO
	Displacement [cm³]	-	-	121	121	121
	Euro Emission Class	-	-	€6.4	€6.4	€6.4
	Gearbox	-	-	eDCT	eDCT	eDCT
	Fuel Tank [L]	-	-	44l	44l	44l